



INSTALLATION INSTRUCTIONS

LD3005

[Model 2013-2021 Dodge Durango w/o 3rd Seat]

1. For any combination style lock, it is a good idea to set the combination before installing the safe. We recommend that the combination be set with the **DOOR OPEN** in order to test the lock combination effectively without locking yourself out.
2. To properly insert the safe, all the plastic in the rear of the vehicle (from behind the 2nd row seats to the rear of the interior of the vehicle) must be removed.
3. Unscrew the proximity sensor from the rear of the compartment for now.
4. Using PVC pipe or 2x4's as a guide rail, slide the safe into the rear of the vehicle.
 - a. To ensure that the safe is set into the vehicle properly, make sure that the mounting brackets line up with the factory holes where the 3rd row seat was secured to the vehicle.
5. Place the **2 LOCK'ER DOWN PROVIDED ½ NUTS** onto the studs, but **DO NOT TIGHTEN YET**.
6. The **2 LOCK'ER DOWN PROVIDED ½ INCH NUTS** allow you to adjust the height of the safe so that it sits flush with the interior trim.
7. Once the safe height has been set, align the front and the rear of the safe with the rear of the vehicle respectively, then secure the safe to the vehicle using the **LOCK'ER DOWN PROVIDED NUTS** placed over the ½ inch nuts on the studs.
 - a. Tighten the nuts to ensure it is securely set, **DO NOT OVER TIGHTEN AS THIS COULD DAMAGE THE VEHICLE OR THE SAFE!**
8. Enjoy your purchase!

Tools Needed:

- **IMPACT DRILL** or **SOCKET WRENCH**
- 13mm Socket Bit and ½ Inch Socket Bit

Contents Included: **2** ½ Inch Nuts.

2 13mm nuts

